

# MONOCOAT Oil Plus 2C

PROTECTS AND COLORS YOUR WOOD IN ONE LAYER

## DESCRIPTION:

**Rubio Monocoat Oil Plus 2C** is a 2-component oil finishing system, consisting of **Monocoat Oil Plus (A)** and **Accelerator (B)** that is very suitable for indoor applications which require quick curing. **Monocoat Oil Plus 2C** is applied in one layer and cures in 5 days. This product is also extremely suitable for industrial applications, both with oxidative and UV processes.

## DIRECTIONS FOR USE:

- 1) Sand the planks. Screen with 80 or 100 grit materials. When renovating old floors, the previous finishes should be removed completely.
- 2) Vacuum the floor.
- 3) Clean the floor with **Monocoat Raw Wood Cleaner** and leave to dry. We recommend you to use the **Raw Wood Cleaner** sparingly to decrease the drying time.
- 4) The system is used in a 3:1 mixture. Pour half of the **Oil Plus (A)** into a large bucket. Add the **Accelerator (B)** to the remaining half of the oil in the can. Close the lid and shake very well. Add the pre-mixed quantity to the **Oil Plus** in the bucket. Stir until you get a homogeneous mass. Apply the **Oil Plus** with a cotton cloth, a brush or a buffer and white pad. The excess oil needs to be removed after 10 minutes, so only treat a 100 s.f. or smaller area.
- 5) After spreading the oil, the excess then needs to be removed, after 10 minutes, until it practically feels dry. Remove the excess oil manually with a cotton cloth or with a buffer supplied with a cotton cloth under a white pad. Try and work in the direction of the wood (i.e. the length of the planks). If you walk on the treated areas while removing the excess, be sure to polish away the footprints.
- 6) The floor can be walked on after 24-36 hours and after 36 hours furniture can be moved in place. During the first week the floor should be maintained with a dust mop or vacuum cleaner. After this week, the floor should be maintained with water and **Monocoat Soap**.

After mixing Oil Plus 2C can be used for a maximum of 6 hours (depending on the temperature and air humidity).

## SPECIFIC FEATURES:

- Molecular bonding with the wood: durable protection!
- 100 % VOC-FREE!
- Respects the natural 'look and feel' of the wood
- Low consumption
- No starting marks or overlaps
- Easy to maintain
- Doesn't contain water
- Applies to all kinds of wood, including furniture and floors (solid wood, veneer wood, MDF, etc...)
- Durable protection, highly resistant to wear
- Water-resistant: (suited for kitchens, bathrooms)
- Resistant to heat up to 212 °F
- Fast curing

## CONSUMPTION:

Depending on the wood type, sanding and application method:

Pure(clear) Oil: +/- 500 s.f. per liter,  
Color Oils: +/- 350 s.f. per liter.

## INDUSTRIAL APPLICATIONS:

For application with oxidative and UV drying systems. The equipment used can be cleaned with **Monocoat Raw Wood Cleaner**.

## TECHNICAL CHARACTERISTICS:

**Oil Plus 2C (A)**- Physical state at 20 °C: liquid  
Odor: natural oil  
Color: transparent

**Accelerator (B)**- Physical state: liquid  
Color: colorless to pale yellow  
Odor: none

Flash point: >160°C (closed cup)

## PACKAGING:

Combined can of 1.3 liter:  
1 L. Oil Plus and .3 L Accelerator.

## STORAGE:

The product can be stored up to 12 months in dry conditions and in its original packaging.

**The product may NOT be diluted!**  
**Cloths, saturated with oil, may spontaneously combust.**  
**After usage, they need to be soaked in water before disposal.**