

Rubiomonocoat OIL PLUS 2C



PROTECTS AND COLORS YOUR WOOD IN ONE SINGLE LAYER

DESCRIPTION:

Rubio Monocoat Oil Plus 2C is a product of the newest generation which colors your wood and protects it in one layer. The combination of the oil (A) and the accelerator (B) guarantees a quick drying. Can also be applied as renovation and maintenance oil on surfaces which are treated with RMC Oil.

SPECIFIC FEATURES:

- Colors and protects in 1 layer
- 40 standard colors that can be blended for unlimited possibilities
- Enhances the natural look and feel of the wood
- Environmentally friendly 100% VOC-FREE!
- Does not contain any water or solvents
- Easy to maintain
- No overlaps or starting marks
- Durable protection, highly resistant to wear
- Low consumption
- Can be applied to all wood types, furniture as well as floors (solid wood, veneer, MDF, etc..)
- Water-resistant, ideal for kitchens and bathrooms
- Heat-resistant up to 212 °F
- Very fast curing: 80% in 2 days
- A short "dry" maintenance period: after 5 days, the surface can be cleaned with water and soap.

DIRECTIONS FOR USE:

1. Sand wood with 80 or 100 grit materials. When renovating old floors, the previous finishes should be removed completely.
2. Vacuum thoroughly
3. Clean the floor with Rubio Monocoat Raw Wood Cleaner and leave to dry. *We recommend you use the Raw Wood Cleaner sparingly to decrease the drying time.
4. The system is used in a 3:1 mixture. Pour half of Oil Plus (A) into a large bucket. Add the Accelerator (B) to the remaining half of the oil in the can. Close the lid and shake very well. Add the pre-mixed quantity to the Oil Plus in the bucket. Stir until you get a homogeneous mass. Apply the Oil Plus with a cotton cloth, a brush or a buffer and white pad. The excess oil needs to be removed after 10 minutes, so only treat a 100 sqft or smaller area at a time.
5. Let absorb for a few minutes. Thoroughly remove all excess oil after 10 minutes. using a cotton cloth or a polishing machine with a white pad. The surface should feel dry! Try to work in the direction of the wood (i.e. the length of the planks). If you walk on the treated areas while removing the excess, be sure to polish away the footprints.
6. The floor can be walked on after 24-36 hours. Furniture can be placed after 36 hours. During the first week, the floor should be maintained with a dust mop or vacuum cleaner. After this week, the floor should be maintained with water and Rubio Monocoat Soap.

DISCLAIMER: It is the responsibility of the user to determine through own testing whether the product is suited for its chosen application. Muylle Facon NV is not liable for any resultant damage. The above information may be subject to amendments, which will be published in revised versions of the technical sheet. We waive all responsibility for unsatisfactory results that are due to causes unrelated to the quality of the product. This technical information has been collected on the basis of current information and knowledge. The most recent technical sheets can be requested or are available on the website.



Consult the safety sheet before use.
Date TDS: 09/09/14

MUYLLE FACON

MADE IN BELGIUM by N.V. MUYLLE - FACON S.A.
Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)
Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78 - HRK 1823
info@muyllefacon.be - www.rubiomonocoat.com

In order to guarantee a long lifespan and protection, the use of Rubio Monocoat maintenance products is imperative.

The equipment used can be cleaned with RMC Cleaner.

CONSUMPTION:

Depending on the wood type, sanding and application method.

Pure(clear) Oil: +/- 500 sqft per liter

Color Oils: +/- 350 sqft per liter

RMC Oil Plus 2C may be used for a maximum of 4 - 6 hours after mixing.

INDUSTRIAL APPLICATIONS:

For application with oxidative and UV drying systems. 645- 861 sqft per liter. These usages are merely indicative. Results depend on wood type and method of preparation. It is always recommended to make a sample in order to calculate the exact usage.

TECHNICAL CHARACTERISTICS:

RMC Oil Plus 2C (A)

Physical state at 68 °F: liquid

Odor: oily

Flash point: > 210°F

Density: > 0,9 kg/L

VOC content: 0 g/L

RMC Accelerator (B)

Physical state at 68 °C: liquid

Color: clear

Odor: none

Flash point: > 320 °F (closed cup)

VOC content: 0 g/L

PACKAGING:

Combined can of 1.3 liter:

1 L. Oil Plus and .3 L. Accelerator.

STORAGE:

The product can be stored up to 24 months in dry conditions and in its original packaging.

ATTENTION:

The product may NOT be diluted!
Cloths, saturated with oil, may spontaneously combust.
After usage, they need to be soaked in water before disposal.

PROVIDED BY:

MONOCOAT.US
© Division of Special Hardwood Products, Inc.
1-877-928-9663

info@monocoat.us
www.monocoat.us

